



CUSHMAN®

HAULER[®] 1200X



GET RED UP TO CONQUER YOUR TO-DO LIST.

With a no-nonsense attitude, the Hauler[®] 1200X lends more than a hand on your toughest work days. Standard features include a lifted suspension for added ground clearance, optional all-terrain tires, and a 1200-lb total load capacity complemented by its smooth ride and ergonomic seats. From transporting equipment to facilitating property maintenance, the Hauler 1200X is a force to be reckoned with and offers reliability you can count on.

13.5HP
KAWASAKI
GAS ENGINE

1200LB
TOW
CAPACITY

12 CU FT
CARGO
BED

900LB
BED LOAD
CAPACITY



H AULER[®] 1200X



HIGHER GROUND CLEARANCE



HITCH RECEIVER



LIGHTS & BRUSH GUARD



OPTIONAL ALUMINUM BED/POWER DUMP

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights
- Tail Lights
- E-Shield □ Frame
- Fuel/Oil Gauge
- Premium Steering Wheel



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

BODY & CHASSIS	
FRAME	Welded Steel with DuraShield □ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	119 in (302.3 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/ CANOPY	77 in (195.6 cm)
WHEEL BASE	77.5 in (196.9 cm)
FRONT WHEEL TRACK	38.0 in (96.5 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	7 in (17.8 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m ³)
POWER	
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal
AIR CLEANER	Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6.0 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Foward) 15.78:1(Reverse)
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	1003 lb (455 kg)
BED LOAD CAPACITY	500 lb (227 kg)
VEHICLE LOAD CAPACITY	900 lb (408 kg)
SPEED	16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph)
TOWING CAPACITY	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	23.5 ft (7.2 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	20 x 8.00 -10