



CUSHMAN®

# HAULER<sup>®</sup> 1200



## LOADED WITH RELENTLESS FUNCTIONALITY.

The Hauler<sup>®</sup> 1200 is equipped to tackle the burden of any job, with a rugged truck-like design. A 12-cubic foot roto-molded bed can easily be customized for every task. Featuring tie-down locations, divider slots and a full line of affordable accessories, transporting everything from loose gravel to small equipment has never been easier. You work hard every day. Let the Hauler 1200 carry the load.

**13.5HP**  
KAWASAKI  
GAS

**1500LB**  
TOW  
CAPACITY

**12 CU FT**  
CARGO  
BED

**1200LB**  
LOAD  
CAPACITY



# CUSHMAN® HULER<sup>®</sup> 1200



OPTIONAL LADDER RACK/ALUMINUM BED



SIDE FILL GAS TANK



OPTIONAL HYDRAULIC BRAKES



VERSATILE DASH STORAGE

## OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet\*
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard\*
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights\*
- Tail Lights\*
- 20" Improved surface tires\*
- Large Fender Flare\*
- E-Shield Frame\*
- Fuel/Oil Gauge\*
- Premium Steering Wheel\*

\*Included in Commercial Package



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

BODY & CHASSIS	
FRAME	Welded Steel with DuraShield Powder Coat
BODY & FINISH	Injected Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	115 in (292.1cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/ CANOPY	70.5 in (179.1 cm)
WHEEL BASE	76.8 in (195.1 cm)
FRONT WHEEL TRACK	35 in (88.9 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	3.5 in (8.9 cm)
CARGO BOX CAPACITY	12 cu ft (0.34m <sup>3</sup> )
POWER	
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal Start
AIR CLEANER	Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	980 lb (445 kg)
BED LOAD CAPACITY	800 lb (363 kg)
VEHICLE LOAD CAPACITY	1200 lb (545 kg)
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)
TOWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	18 x 8.5-8