



**CUSHMAN**<sup>®</sup>

# H AULER<sup>®</sup> PRO-X



## GET MORE MILE GE OUT OF EVERY WORK D Y.

Stand back and let the new Hauler<sup>®</sup> PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PRO-X will help you and your team work seamlessly without disrupting your environment. Outstanding energy efficiency, low operational costs and a dash that easily accommodates radios, clip boards, oversized beverage containers and more, the Hauler PRO-X is equipped for action.

**72V**  
AC  
ELECTRIC

**1200LB**  
TOW  
CAPACITY

**12 CU FT**  
CARGO  
BED

**900LB**  
LOAD  
CAPACITY



# H AULER<sup>®</sup> PRO-X



HIGHER GROUND CLEARANCE



STANDARD ON BOARD CHARGER



ROTO-MOLDED BED



VERSATILE DASH STORAGE

## OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights
- Tail Lights
- 20" Improved surface tires
- E-Shield Frame
- Premium Steering Wheel



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

| BODY & CHASSIS           |  |
|--------------------------|--|
| FRAME                    | Welded Steel with DuraShield Powder Coat   |
| BODY & FINISH            | Injection Molded TPO                       |
| STANDARD COLOR           | Patriot Blue                               |
| DIMENSIONS               |  |
| OVERALL LENGTH           | 119 in (302.3 cm)                          |
| OVERALL WIDTH            | 49.4 in (125.5 cm)                         |
| OVERALL HEIGHT W/ CANOPY | 77 in (195.6 cm)                           |
| WHEEL BASE               | 77.5 in (196.9 cm)                         |
| FRONT WHEEL TRACK        | 38.0 in (96.5 cm)                          |
| REAR WHEEL TRACK         | 38.0 in (97.8 cm)                          |
| GROUND CLEARANCE         | 7.2 in (18.29 cm)                          |
| CARGO BOX CAPACITY       | 12 cu ft (.034 m <sup>3</sup> )            |
| POWER                    |  |
| POWER SOURCE             | 72-Volts                                   |
| MOTOR TYPE               | AC Induction                               |
| HORSEPOWER (KW)          | 22.4HP (16.7 kW) - Measured at Peak Torque |
| ELECTRICAL SYSTEM        | 72 Volt                                    |
| BATTERY (QTY/TYPE)       | Nine 8-Volt Deep Cycle                     |
| BATTERY CHARGER          | 900 Watt 72V DC                            |
| KEY OR PEDAL START       | Pedal                                      |
| DRIVE TRAIN              | Motor Shaft Direct Drive                   |
| TRANSAXLE                | Differential with Helical Gears            |
| SPEED CONTROLLER         | 350 Amp AC                                 |
| GEAR SELECTION           | Forward-Neutral-Reverse                    |
| REAR AXLE RATIO          | 17:1                                       |
| PERFORMANCE              |  |
| SEATING CAPACITY         | 2 Person                                   |
| CURB WEIGHT              | 1513 lb (686 kg)                           |
| BED LOAD CAPACITY        | 500 lb (227 kg)                            |
| VEHICLE LOAD CAPACITY    | 900 lb (408 kg)                            |
| SPEED                    | 16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph)    |
| TOWING CAPACITY          | 1200 lb (544 kg) max                       |
| OUTSIDE CLEARANCE CIRCLE | 23.5 ft (7.2 m)                            |
| STEERING & SUSPENSION    |  |
| STEERING                 | Self-Compensating Rack and Pinion          |
| FRONT/REAR SUSPENSION    | Leaf Springs w/ Hydraulic Shock Absorbers  |
| SERVICE BRAKE            | Rear Wheel Mechanical Self-adjusting Drum  |
| PARKING BRAKE            | Self-compensating, Single Point Engagement |
| FRONT/REAR TIRES         | 20 x 8.0 -10                               |