



**CUSHMAN®**

# SHUTTLE<sup>□</sup> 4



## MOVE PEOPLE AND GEAR WITH EASE.

If you need a general-purpose vehicle to move around your facility, look no further than the Cushman® Shuttle™ 4. It combines four forward-facing seats with a spacious cargo bed for efficient transport of personnel and equipment. Available in both a 48V electric model and a gas-powered option with a 13.5 hp Kawasaki® engine, the Shuttle 4 keep passengers and their gear comfortable on the move.

**13.5HP**  
KAWASAKI®  
GAS ENGINE  
OPTION

**48V**  
ELECTRIC  
DRIVETRAIN  
OPTION

**1200LB**  
TOTAL LOAD  
CAPACITY





# CUSHMAN® SHUTTLE<sup>□</sup> 4



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION  
STEERING

## OPTIONS & ACCESSORIES

- Rear View Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pin Stripes
- Body Color  
(Forest Green, White  
or Custom Options)
- Turn Signal with  
Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers - Spoke  
and Chrome
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN  
CARE TOTAL PROTECTION WARRANTY

### ELECTRIC MODEL

### GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield <sup>□</sup> Powder Coat
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	135.0 in (343 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
CARGO DECK CAPACITY	9 cu ft (.25 m <sup>3</sup> )
CARGO DECK MATERIAL	Wood Stake Sides
POWER	
POWER SOURCE	48V DC
VALVE TRAIN	N/A
HORSEPOWER (KW)	18.1 hp (13.5 kW) Intermittent
ELECTRICAL SYSTEM	48V
BATTERY (QTY/TYPE)	Eight, 6V Deep Cycle
BATTERY CHARGER	48 VDC Delta Q, 120/230V AC, UL & CSA
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A
LUBRICATION	N/A
OIL FILTER	N/A
COOLING SYSTEM	N/A
FUEL CAPACITY	N/A
SPEED CONTROLLER	400 Amp Precision Drive System (PDS)
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	14.7:1
PERFORMANCE	
SEATING CAPACITY	4-Person
WEIGHT W/O BATTERIES	720 lb (327 kg)
CURB WEIGHT	1200 lb (544 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	400 lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	13 mph ± 0.5 mph (21 kph ± 0.8kph)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Links 18 x 8.5 - 8 (4 Ply Rated)