



CUSHMAN®

SHUTTLE[®] 6



TRANSPORT LARGE GROUPS EFFICIENTLY.

The Cushman® Shuttle™ 6 is the go-to vehicle for moving people throughout a facility. With four forward-facing seats and a rear-facing bench seat, it can transport up to six people quickly and comfortably. Available with either a 48V electric drivetrain or a 13.5 hp Kawasaki® gas-powered engine, the Shuttle 6 will ensure your crew and guests will arrive and depart in style.

13.5HP
KAWASAKI®
GAS ENGINE
OPTION

48V
ELECTRIC
DRIVETRAIN
OPTION

6
PERSON
SEATING
CAPACITY



CUSHMAN® SHUTTLE 6



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rear View Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pin Stripes
- Body Color (Hunter Green, Champagne or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield <input type="checkbox"/> Powder Coat
BODY & FINISH	Injection Molded TPO (Front) Steel Base Coat/Clear Coat (Rear)
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	136.0 in (345 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
POWER	
POWER SOURCE	48V DC
VALVE TRAIN	18.1 hp (13.5 kW) Intermittent
HORSEPOWER (KW)	48V
ELECTRICAL SYSTEM	Eight, 6V Deep Cycle
BATTERY CHARGER	48V DC Delta Q, 120/230V AC, UL & CSA
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A
LUBRICATION	N/A
OIL FILTER	N/A
COOLING SYSTEM	N/A
FUEL CAPACITY	N/A
SPEED CONTROLLER	400 Amp Precision Drive System (PDS)
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	14.7:1
PERFORMANCE	
SEATING CAPACITY	6-Person
WEIGHT W/O BATTERIES	890 lb (403 kg)
CURB WEIGHT	1385 lb (628 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	13 mph ± 0.5 mph (21 kph ± 0.8kph)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Links 18 x 8.5 - 8 (4 Ply Rated)