



SHUTTLE[□] 2+2

MOVING PEOPLE, SAVING TIME.

The Cushman Shuttle 2+2 is the ideal choice for transporting personnel and visitors around a plant, resort, or the jobsite. Comfortably seating up to four passengers with generous bench seating, the rear seat will also convert to a cargo space. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp Kawasaki gas-powered engine, or 48-volt electric power drivetrain.

13.5HP
GAS OR
48V ELECTRIC

14MPH
MAX
SPEED

800LB
LOAD
CAPACITY



CUSHMAN® SHUTTLE[□] 2+2



**BRUSH GUARD
AND HEADLIGHTS**



**CONVERTIBLE REAR SEAT
TO CARGO AREA**

BRAKE LIGHTS (OPTIONAL)



**WINDSHIELD AND
CANOPY (OPTIONAL)**

OPTIONS & ACCESSORIES

- LED Headlights
- 4-Way Turn Signals
- Sun Canopy
- Windshield
- Weather Enclosure
- Hour Meter
- 12 Volt Outlet
- Strobe Light
- Locking Glove Box Door
- Rear Mirrors

BODY & CHASSIS	ELECTRIC	GAS
FRAME	Welded steel with DuraShield [□] powder coat	Welded steel with DuraShield [□] powder coat
BODY & FINISH	Injection Molded TPO	Injection Molded TPO
STANDARD COLOR	Patriot Blue	Patriot Blue
DIMENSIONS		
OVERALL LENGTH	108.5 in (276 cm)	108.5 in (276 cm)
OVERALL WIDTH	48.5 in (123 cm)	48.5 in (123 cm)
OVERALL HEIGHT	46.5 in (118 cm) (Top of steering wheel)	46.5 in (118 cm) (Top of steering wheel)
OVERALL HEIGHT (w/ CANOPY)	77.0 in (196cm) (Top of Sun Canopy)	77.0 in (196cm) (Top of Sun Canopy)
WHEEL BASE	65.5 in (166 cm)	65.5 in (166 cm)
FRONT WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)
REAR WHEEL TRACK	38.5 in (98 cm)	38.5 in (98 cm)
GROUND CLEARANCE	4.5 in (11 cm)	4.5 in (11 cm)
LOAD DECK WIDTH	40.0 in (102 cm)	40.0 in (102 cm)
LOAD DECK LENGTH	32.0 in (81 cm)	32.0 in (81 cm)
POWER		
POWER SOURCE	48 Volts DC	4 Cycle 24.5 cu in (401 cc).
MOTOR TYPE	Shunt Wound	Single Cylinder OHV
HORSEPOWER (KW)	3.0 HP (2.2kW) Continuous	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48 Volt	Starter/Generator. Solid State Regulator
BATTERY (QTY/TYPE)	Six, 8 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	Pedal
AIR CLEANER	N/A	Replaceable Dry Cartridge
SPEED CONTROLLER	250 Amp Solid State Controller	N/A
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	6.0 Gallon (22.7 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	Dash Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	12.44:1	11.42:1 (Forward) 15.78:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	4 Person	4 Person
CURB WEIGHT	1036 lb (470kg)	896 lb (406 kg)
DRY WEIGHT	658 lb (298kg)	861 lb (391 kg)
DECK LOAD CAPACITY	250 lb (113 kg)	250 lb (113 kg)
VEHICLE LOAD CAPACITY	800 lb (363 kg)	800 lb (363 kg)
OUTSIDE CLEARANCE CIRCLE	19 ft (5.8 m)	19 ft (5.8 m)
SPEED	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)
STEERING & SUSPENSION		
STEERING	Self-compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TIRES	18 x 8.50 - 8 (4-Ply Rated)	